

OSLO CARRIER 3



General particulars



General info

Built:	2011
Port of Registry:	Oslo
Flag:	NIS
IMO no:	9366146
Class:	DNV GL
Owners P+I Club:	Gard Oslo

Tonnage

Dwt:	9.828 dwt
GT/NT:	6.668 / 3.625
Displacement:	13362,84
Panama net:	5670
Suez net:	5857

Speed / Consumption

Abt. 11 knots on abt. 13 mts IFO 380 cSt at sea or manoeuvring
Abt. 1,5 mt of MGO idle / abt. 2,5 mts MGO when working cranes

Above parameters are based in good weather conditions whilst vessel is on even keel, maximum Force 3 in Beaufort scale and sea-state 2 in Douglas scale. No negative currents, swells or tidal streams, and in temperate waters

All details are "about" and given in good faith without guarantee

IMDG dangerous cargoes can be loaded in:

Cargo holds No. 1-3:

Class 1.4s, 2.1, 2.2, 2.3, 3.3, 4.1, 4.2, 4.3, 5.1, 6.1, 8, 9

Class 1.1-1.6, 5.2 allowed on deck

Capacity

Grain	1: 2.988 cbm / 105.536cb.ft	2: 4.567 cbm / 161.306cb.ft	3: 4.567 cbm / 161.306cb.ft	Total: 12.120 cbm / 428.148cb.ft
-------	-----------------------------	-----------------------------	-----------------------------	----------------------------------

Type

SINGLEDECKER OPEN HATCH/BOXY BULKER

Dimensions

LOA:	107,00 m
LPP:	103,00 m
Beam:	18,20 m
Draft Summer:	8,29 m SSW
Depth moulded:	10,50 m
WLTHC:	6,8m hold 1 - 5,1m hold 2&3

Engine

Main engine:	MAK 8M32C - 3840KW
Aux. Engine:	2 x 399 kW
Shaft generator:	500 kW
Bow thruster:	Yes - 450 kW FPP

Tank capacity

FuFuel IFO:	584 m3
Fuel GO:	127 m3
Fresh water:	136 m3
Ballast:	2,980 m3

Containers

Deck : 132 TEU

Gear

Type of gear: 2 x 60 mt cranes

Mechanical ventilation system:

10 changes pr hrs basis empty holds

Holds

Number of Holds: 3

Hold capacity, dimensions (L X B X H): HO 1: 16,1 m X 15,2 M narrowing fwd to 10,3 m, Height: 13,1 m

HO 2: 25,9 m X 15,2 m - pure box Height: 11,6 m

HO 3: 25,9 m X 15,2 m - pure box Height: 11,6 m

Hatch

Hatch openings: No 1: 16,1 m x 15,2 m
No 2: 25,9 m x 15,2 m
No 3: 25,2 m x 15,2 m

Type of covers: McGregor

Permissible Loads

Tanktop:	14 mt/sqm
Tweendeck pontoons:	1,75 mt/sqm

Hold Equipment

IMO Fitted:	as per Document of Compliance
Hold ladders:	Hold ladders in bulk head AMSA approved except for slanted ladders
St Lawrence fitted:	No
Smoke detector fitted:	Yes